

OUR CABIN LIFT WITH AUTOMATIC RUN

Aritco 9000

Datasheet 2024

Aritco 9000 is our cabin lift for the accessibility market. The lift is designed to meet all requirements for quality, safety and service. It is a perfect fit for tough and demanding environments such as schools, shops and residential buildings.

Several advantages offered by Aritco 9000:

- Design, sizes and options tailored to public environments
- 95% recyclable materials
- Patented screw/nut technology (no oil that can leak)
- The lowest maintenance and operating costs on the market
- Cabin control: Automatic "one-touch"

For more information please visit aritco.com



ARITCO™

Aritco Lift AB
Elektronikhöjden 14, Box 516
175 26 Järfälla, Sweden

T: +46 (0) 8 120 401 00
E: info@aritco.com
www.aritco.com

Explore ARITCO 9000




Key features


Aritco 9000 comes with customization possibilities. When it comes to design and possibility to customize the lift, you can choose from more than 200 different colours, 2 different glass types and 7 different floors. The lift is very practical and smart and gives everyone access to different floors in public & commercial buildings. It comes in two different sizes, in which you can fit a stroller or a wheelchair. It's reliable and has a robust design that can handle tough public & commercial environments. The lift is equipped with our SmartSafety system, with safety features, to meet all situations that can occur in public & commercial spaces, as well as to prevent accidents.

Sizes

Size: 1000 x 1400 mm
Rated load: 400 kg / 5 pers.
Wheelchair: A or B with attendant*



Size: 1100 x 1400 mm
Rated load: 400 kg / 5 pers.
Wheelchair: A or B with attendant, adjacent entry*



* National guidelines may apply. Wheelchair Type A and B according to EN 12183/EN 12184

Lift color

Can be painted in any RAL colour from the Chart K7 classic chart (except for pearl and fluorescent colours)



Cabin color

22 different wall- and ceiling laminates to choose from.



Glass

2 different glass types to choose from.

STANDARD
Clear glass



Tinted glass



Floor

7 different floorings to choose from.



Installation environment:

Indoor

Type of lift

Platform lift intended for installation in public and commercial environments

Drive system

Patented screw-and-nut system

Motor

3 kW motor

Rated speed

Max 0.15m/s inside Europe

Technical compliance

European Machine directive 2006/42/EC

Emergency lowering

Battery-powered

Travel height

2150¹⁾ -13000 mm
1) For opposite entry. 2300 mm when doors on same side

Top height

Min. 2 400

Number of floors

2 to 6 floors

Installation

Recessed installation 75 mm below floor
Installed directly on the floor with ramp

Operation

Control from carrier control panel. – Press one time to operate lift

Power supply

400 V 3-phase

Warranty

Aritco 9000 comes with a 5-year product warranty and a 10-year drive technology warranty.

