

# OUR MOST COMPACT HOME LIFT

## Aritco 4000

Datasheet 2022

The lift has been designed to meet all requirements for comfort, space and design. The lift is available in different sizes, with an option to personalise it with details such as glass walls, a range of varied colours and different materials.

### Several advantages offered by Aritco 4000:

- Design, sizes and options created for a home environment
- Minimum interventions in the house
- 95% recyclable materials
- Patented screw/nut technology (no oil that can leak)
- The lowest maintenance and operating costs on the market

For more information please visit [aritco.com](http://aritco.com)



  
**ARITCO™**

**Aritco Lift AB**  
Elektronikhöjden 14, Box 516  
175 26 Järfälla, Sweden

T: +46 (0) 8 120 401 00  
E: [info@aritco.com](mailto:info@aritco.com)  
[www.aritco.com](http://www.aritco.com)

# Explore


## Aritco 4000



### Key features

Aritco 4000 comes with several customization options to personalize your lift. You can choose between more than 200 different colors, two different glass types and eight different floorings. The lift is also very compact and space-efficient, which makes it possible to install the lift in almost any home, even where space is limited. The lift is equipped with our SmartSafety system, with safety features that anticipate situations and prevent accidents.

### Sizes



MODEL	CARRIER SIZE	EXTERIOR DIMENSIONS	RATED LOAD
<b>1</b>	580 x 805 mm	840 x 880 mm	250 kg / 2 persons
<b>2</b>	880 x 805 mm	1140 x 880 mm	250 kg / 2 persons
<b>3</b>	1080 x 805 mm	1340 x 930 mm	250 kg / 2 persons

### Lift color

Can be painted in any RAL color from the RAL K7 classic chart (Except for pearl and fluorescent colors)



### Glass

STANDARD  
Clear glass



OPTIONAL  
Tinted



### Floor



### Intended use

Installation in private homes  
Indoor installation environments

### Technical compliance

European Machine Directive 2006/42/EC  
European Standard EN 81-41

### Drive system

Patented screw-and-nut system

### Rated speed

Max 0.15 m/s

### Emergency lowering

Battery-powered

### Travel height

250 - 13 000 mm

### Top height

Min. 2 300 mm

### Number of floors

2 to 6 floors

### Installation

Recessed installation 50 mm below floor level  
Installed directly on floor with 50 mm ramp

### Operation

Hold to run (press and hold)  
One-touch operation (press one time) for installations outside Europe

### Power supply

230 V 1-phase

### Warranty

Aritco 4000 comes with a 5-year warranty.  
The screw-and-nut assembly has a 10-year warranty

