

ACCESSIBILITY IN PUBLIC & COMMERCIAL BUILDINGS

Aritco PublicLift Access

Datasheet 2022

Aritco PublicLift Access is designed to make public and commercial buildings accessible for everyone. The lift expresses Scandinavian design and features a backlit panel and lit handlebar.

Advantages offered by Aritco PublicLift Access:

- Design, sizes and options tailored for public environments
- 95% recyclable materials
- Patented screw and nut technology (no oil that can leak)
- The lowest maintenance and operating costs on the market
- Equipped with our SmartSafety system with safety features for public environments

For more information please visit aritco.com



Aritco Lift AB
Elektronikhöjden 14, Box 516
175 26 Järfälla, Sweden

T: +46 (0) 8 120 401 00
E: info@aritco.com
www.aritco.com

Explore

Aritco PublicLift Access



Key features

Alternative models

OUTDOOR version
GOODS version

Aritco PublicLift Access comes with customization possibilities. Choose from more than 200 different colours, 2 different glass types and 8 different floors. The lift is very practical and smart and gives everyone access to different floors in public & commercial buildings. It comes in several different sizes, and on the larger ones you can fit a stroller or a wheelchair. It's reliable and has a robust design that can handle tough public & commercial environments. The lift is equipped with our SmartSafety system, with safety features, to meet all situations that can occur in public & commercial spaces, as well as to prevent accidents.

Sizes

| MODEL | CARRIER SIZE | EXTERIOR DIMENSIONS | RATED LOAD | WHEELCHAIR |
|----------|----------------|---------------------|--------------------------|--|
| 1 | 900 x 1040 mm | 1300 x 1160 mm | 250 kg / 2 persons | - |
| 2 | 900 x 1280 mm | 1300 x 1400 mm | 410 kg / 5 persons | Lone user or type A* |
| 3 | 900 x 1480 mm | 1300 x 1600 mm | 410, 500 kg / 5, 6 pers. | A or B with attendant* |
| 4 | 1000 x 1280 mm | 1400 x 1400 mm | 410 kg / 5 persons | Lone user or type A* |
| 5 | 1000 x 1480 mm | 1400 x 1600 mm | 410, 500 kg / 5, 6 pers. | A or B with attendant* |
| 6 | 1100 x 1480 mm | 1500 x 1600 mm | 410, 500 kg / 5, 6 pers. | A or B with attendant, adjacent entry* |
| 7 | 1000 x 1980 mm | 1400 x 2100 mm | 500 kg / 6 persons | A or B with attendant* |
| 8 | 1100 x 1580 mm | 1500 x 1700 mm | 500 kg / 6 persons | A or B with attendant, adjacent entry* |

* National guidelines may apply. Wheelchair Type A and B according to EN 12183/EN 12184.

Lift color

Can be painted in any RAL color from the RAL K7 classic chart (Except for pearl and fluorescent colours)



Glass

2 different glass types to choose from.

STANDARD
Clear glass



OPTIONAL
Tinted glass



Floor

8 different floorings.



Installation environment:

Indoor

Type of lift

Platform lift intended for installation in public and commercial environments.

Drive system

Patented screw-and-nut system

Motor

2.2 kW motor

Rated speed

Max 0,15 m/s inside Europe
Max 0,25 m/s outside Europe

Technical compliance

European Machine directive 2006/42/EC
European standard EN 81-41

Emergency lowering

Battery-powered.

Travel height

250 - 13 000 mm

Top height

Min. 2 240

Number of floors

2 to 6 floors

Installation

Recessed installation 50 mm below floor
Installed directly on the floor with 50 mm ramp

Operation

Hold to run - press and hold
For installations outside Europe - One touch operation (press one time)

Power supply

230 V 1-phase
400 V 3-phase

Warranty

Aritco PublicLift Access comes with a 5-year warranty.
The screw-and-nut assembly has a 10-year warranty

Alternative model

Aritco PublicLift Access GOODS version is a version of the Aritco PublicLift Access lift that is intended for both persons and goods.
Aritco PublicLift Access OUTDOOR version is designed for outdoor use. All outdoor lifts are delivered with corrosion class C5 guides to avoid corrosion.
For more information please visit aritco.com