OUK CABIN LIFT WITH AUTOMTIC RUN

Aritco 9000 Datasheet 2025

Aritco 9000 is our cabin lift for the accessibility market. The lift is designed to meet all requirement for quality, safety and service. It is a perfect fit for tough and demanding environments such as schools, shops and residential buildings. **Several advantages offered by Aritco 9000:**

- Design, sizes and options tailored to public environments
- 95% recyclable materials
- Patented screw/nut technology (no oil that can leak)
- The lowest maintenance and operating costs on the market
- Cabin control: Automatic "one-touch"

For more information please visit **aritco.com**











Aritco Lift AB Elektronikhöjden 14, Box 516 175 26 Järfälla, Sweden

T: +46 (0) 8 120 401 00 E: info@aritco.com www.aritco.com

Explore **ARITCO 9000 Key features** Aritco 9000 comes with customization possibilities. When it comes to design and possibility to customize the lift, you can choose from more than 200 different colours, 2 different glass types and 7 different floors. The lift is very practical and smart and gives everyone access to different floors in public & commercial buildings. It comes in two different sizes, in which you can fit a stroller or a wheelchair. It's reliable and has a robust design that can handle tough public & commercial environments. The lift is equipped with our SmartSafety system, with safety features, to meet all situations that can occur in public & commercial spaces, as well as to

Can be painted in any RAL colour from

the Chart K7 classic chart (except for pearl and fluorescent colours)

Sizes

Lift color

Cabin color

Glass

Floor

22 different wall- and ceiling laminates to choose from.

2 different glass types

7 different floorings to

to choose from.

choose from.

Installation

environment:

Size: 1000 x 1400 mm Rated load: 400 kg / 5 pers. Wheelchair: A or B with attendent*

STANDARD

Clear glass

Indoor

prevent accidents.

* National guidelines may apply. Wheelchair Type A and B according to EN 12183/EN 12184

Size: 1100 x 1400 mm Rated load: 400 kg / 5 pers. Wheelchair: A or B with attendent, adjacent entry*

Type of lift

Tinted glass

Platform lift intended for installation in public and commercial environments

| Drive system | Patented screw-and-nut system |
|----------------------|---|
| Motor | 3 kW motor Rated speed Max 0.15 m/s inside Europe |
| Technical compliance | European Machine directive 2006/42/EC |
| Emergency lowering | Battery-powered |
| Travel height | 2150^v -13000 mm 1) For opposite entry. 2300 mm when doors on same side |
| Top height | Min. 2 400 |
| Number of floors | 2 to 6 floors |
| Installation | Recessed installation 75 mm below floor Installed directly on the floor with ramp |
| Operation | Control from carrier control panel. – Press one time to operate lift |
| Power supply | 400 V 3-phase |
| Warranty | Aritco 9000 comes with a 5-year product warranty and a 10-year drive technology warranty. |



