

OUR CABIN LIFT FOR PUBLIC & COMMERCIAL BUILDINGS

Aritco PublicLift Cabin

Datasheet 2025

The lift is designed with simplicity in mind. It looks, feels, performs and operates like a conventional passenger lift. With no machine room or deep pit required, it offers complete freedom in design and simple usability, providing total safety in use. The energy efficient traction drive and fully automatic telescopic doors make it a versatile, cost effective passenger lifting solution.

Several advantages offered by Aritco PublicLift Cabin:

- Design, size and options tailored for public environments
- Minimum interventions in the building
- One of the lowest maintenance and operating costs on the market
- Cabin control: Automatic "one-touch"
- Eurocode 3 compliant

For more information please visit [aritco.com](https://www.aritco.com)



Aritco Lift AB
Elektronikhöjden 14, Box 516
175 26 Järfälla, Sweden

T: +46 (0) 8 120 401 00
E: info@aritco.com
www.aritco.com

Explore

Aritco PublicLift Cabin*

Key features

The lift is designed with simplicity in mind. It looks, feels, performs and operates like a conventional passenger lift. With no machine room or deep pit required, it offers complete freedom in design and simple usability, providing total safety in use.

The energy efficient traction drive and fully automatic telescopic doors make it a versatile, cost effective passenger lifting solution. Several advantages offered by Aritco PublicLift Cabin: Design, size and options tailored for public environments, Minimum interventions in the building, The lowest maintenance and operating costs on the market, Cabin control: Automatic "one-touch", Eurocode 3 compliant.


Size

1140 x 1400 mm


Wheelchair: A or B

with attendant*

Installed in a masonry shaft



Installed with a self supporting shaft



* National guidelines may apply. Wheelchair Type A and B according to EN 12183/EN 12184.

Doors

2 different door types to choose from. 2- or 3-panel fully automatic telescopic sliding doors in various materials. Fire rated door is optional.

Lift color

Can be painted in any RAL color from the RAL K7 classic chart



Cabin finish

In plastic coated metal sheet



Or painted in any RAL color from the RAL K7 classic chart



Glass

2 different glass types to choose from.

STANDARD
Clear glass



OPTIONAL
Tinted glass



Floor

Select between rubber, vinyl or your own flooring alternative



Installation environment

Indoor & Outdoor

Type of lift

Platform lift intended for installation in public and commercial environments.

Drive system

Double belt traction drive system

Motor

3kW motor, above 7 m travel with counter weight. (option for low usage with 1,5kW motor)

Rated speed

Max 0.15 m/s

Technical compliance

European Machine directive 2006/42/EC
European standard

Emergency lowering

Battery-powered

Travel height

250 – 14 600 mm

Top height

Min. 2 600

Number of floors

2 to 5 floors

Installation

Recessed installation masonry shaft 120 mm, steel structure 140 mm below floor.
Installed directly on floor with ramp

Operation

Control from carrier control panel. Press one time to operate lift

Power supply

230 V 1-phase

Rated load

Max. 450 kg**

Warranty

Aritco PublicLift Cabin comes with a 5-year product warranty and a 10-year drive technology warranty.



*Only available in the UK and Nordic market.

**Max rated load with 3kW motor and above 7 m travel with counter weight, with one standard cabin door (not in glass). Rated load will be reduced to 400 kg for lifts with 2 sliding doors or for lifts with 1 sliding door in glass. For low usage option with 1,5kW motor max rated load is 400 kg (only 1 standard cabin door and 7 m travel possible)